



## Technical Specification/Submittal

# EA Powered Swing Gate

The **EA Powered Swing Gate** can be used as single units or as pairs, allowing the flexibility to create various opening widths to suit the application. Matching glass balustrading is available to close or cordon off unused areas.

Our contemporary powered gate has LED lighting at the top which gives a clear indication of its status. Visually users can see if the gate is locked, in standby or in receipt of an opening signal. Uniquely the locking mechanism has a ratcheting system that allows the gate to move slightly if pressure is applied when locked. This clever feature reduces the chances of glass breakage and the gate illuminates red and a warning alarm is sounded

**EA Powered Swing Gates** can be integrated with both Access Control Units and Fire Alarm Systems, to provide controlled access/egress and or allow free egress in the event of a fire alarm/emergency activation. When integrated with a fire alarm, on fire activation, the leaf or leafes open to allow free exit and remain unlocked until the alarm is reset.

Model No	EA-B508
Size	168x1004mm
Input voltage	240V
Drive motor	DC 24v brushless motor
Operating Cycle	Up to 30 seconds - adjustable
Applicable temperature	-20°C to +70°C
Glass thickness	8mm
Swing direction	Single / Bi-directional
Passage width	906mm. Custom widths also available

## Technical Specification/Submittal

# EA Powered Swing Gate

The **EA Powered Swing Gate** is the simplest and most affordable way to control and restrict access and is available from a 500 to 1850\* mm clear opening. (\*2 gates)

The EA Powered Swing Gate is perfectly suited for access control where a wider access point is required, but is typically controlled by a receptionist who oversees the user

The EA Powered Swing Gate is suitable for disabled and VIP-purpose accesses, these are recommended to be installed next to our tripod turnstiles to provide an unhindered route.

The **EA Powered Swing Gate** is equipped with a servo-actuator that can be controlled in either a manual or automatic mode.

In the manual mode, the gate is opened/closed with a push button or control panel often at a reception desk or a remote position.

In the automatic mode, the gate is opened/closed determined from the signal from an access control system.

The operational principle of this product is based upon the device locking the leaf in its closed position.


When access permission is granted, the actuator rotates the flag-shape leaf to 90 degrees and returns to its initial closed position (Cycle time can be adjusted during installation).

During loss of power, the **EA Powered Swing Gate** unlocks, opens and allows a free passage. Optionally a UPS battery can be installed to keep the gate operational during loss of power.



## Technical Specification/Submittal

# Wiring & Layout Details



### NOTES:

- EA DDA Glass Swing Gate - brushed 304 stainless steel body with brushed aluminium glass clamp. Glass is 10mm toughened.
- Fixings: Cabinets are secured to floor with M10 studding chem-fixed in position; thru Tile, adhesive, screed and into concrete sub-base upto 100mm deep from FFL.





**EA GROUP OFFER A WIDE RANGE OF SECURITY  
AND ACCESS CONTROL SOLUTIONS**

Speed Gates, Revolving & Automatic Doors, Automatic  
Gates, Access Control, CCTV, Rising & Security  
Bollards and Car park & Automatic Vehicle Barriers

**We are also able to offer bespoke access solutions:**

After Sales / Maintenance & product Support packages  
Free quotations  
Customised technical drawings and presentations

*Peace of mind, professional service and product  
warranty from the UK's leading Access Security  
Specialist, Revolving Door, Gate & Barrier  
Automation and CCTV installer*

Visit our website:

**[www.ea-group.co.uk](http://www.ea-group.co.uk)**

for further details or telephone our  
sales and enquiry desk on  
**+44 (0)1372 459536**

**EA Group (UK) Limited**

Units 20/21 Bookham Industrial  
Park Church Road, Bookham  
Surrey, KT23 3EU

Registered in England: 3094251 VAT No: 994124937



Certificate Number 19313

